

**SAFETY DATA SHEET**  
**BC Poxy 300 HD-AS Part-B**

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1. Product identifier**

**Product name**                      **BC Poxy 300 HD Part-B**

**Product number**                **300**

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

**Identified uses**                      Coating

**1.3. Details of the supplier of the safety data sheet**

Building Chemistry Industry

Code 338941

Tel: 0138050533

Mob: 0593120221

Kingdom of Saudi Arabia

**1.4. Emergency telephone number**

**Emergency telephone**            +966 0593120221

**SECTION 2: Hazards identification**

**2.1. Classification of the substance or mixture**

**Classification (EC 1272/2008)**

**Physical hazards**                      Not Classified

**Health hazards**                      Acute Tox. 4 - H302 Skin Corr. 1B - H314 Eye Dam. 1 - H318 Elicitation - EUH208 STOT RE 2 - H373

**Environmental hazards**            Aquatic Chronic 2 - H411

**2.2. Label elements**

**Pictogram**



**Signal word**

Danger

## BC Poxy 300 HD-AS Part-B

### Hazard statements

EUH208 Contains BIS(1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL) SEBACATE. May produce an allergic reaction.  
 H302 Harmful if swallowed.  
 H314 Causes severe skin burns and eye damage.  
 H373 May cause damage to organs through prolonged or repeated exposure.  
 H411 Toxic to aquatic life with long lasting effects.

### Precautionary statements

P260 Do not breathe vapor/ spray.  
 P273 Avoid release to the environment.  
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.  
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.  
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P314 Get medical advice/ attention if you feel unwell.

### Contains

POLY(OXY(METHYL-1,2-ETHANEDIYL)), ALPHA-(2-AM OMEGA-(2-AMINOMETHYLETHOXY, DIETHYLMETHYLBENZENEDIAMINE

### Supplementary precautionary statements

P264 Wash contaminated skin thoroughly after handling.  
 P270 Do not eat, drink or smoke when using this product.  
 P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
 P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.  
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 P321 Specific treatment (see medical advice on this label).  
 P363 Wash contaminated clothing before reuse.  
 P391 Collect spillage.  
 P405 Store locked up.  
 P501 Dispose of contents/ container in accordance with national regulations.

### 2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

**POLY(OXY(METHYL-1,2-ETHANEDIYL)),ALPHA-(2-AM OMEGA-(2-AMINOMETHYLETHOXY**

**60-100%**

CAS number: 9046-10-0

#### Classification

Acute Tox. 4 - H302

Skin Corr. 1B - H314

Aquatic Chronic 3 - H412

## BC Poxy 300 HD-AS Part-B

<b>DIETHYLMETHYLBENZENEDIAMINE</b>		<b>10-30%</b>
CAS number: 68479-98-1	EC number: 270-877-4	
M factor (Acute) = 1	M factor (Chronic) = 1	
<b>Classification</b>		
Acute Tox. 4 - H302		
Acute Tox. 4 - H312		
Eye Irrit. 2 - H319		
STOT RE 2 - H373		
Aquatic Acute 1 - H400		
Aquatic Chronic 1 - H410		
<b>BIS(1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL)SEBACATE</b>		<b>&lt;1%</b>
CAS number: 41556-26-7		
M factor (Acute) = 1	M factor (Chronic) = 1	
<b>Classification</b>		
Skin Sens. 1 - H317		
Aquatic Acute 1 - H400		
Aquatic Chronic 1 - H410		

The full text for all hazard statements is displayed in Section 16.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

<b>General information</b>	Avoid contact with skin and eyes. Do not breathe vapor. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
<b>Inhalation</b>	Move affected person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention if any discomfort continues.
<b>Ingestion</b>	Do not induce vomiting. Give plenty of water to drink. Never give anything by mouth to an unconscious person. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention immediately.
<b>Skin contact</b>	Remove affected person from source of contamination. Wash skin thoroughly with soap and water. Get medical attention if irritation persists after washing.
<b>Eye contact</b>	Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention. Get medical attention if irritation persists after washing.

#### 4.2. Most important symptoms and effects, both acute and delayed

<b>General information</b>	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
----------------------------	---

#### 4.3. Indication of any immediate medical attention and special treatment needed

<b>Notes for the doctor</b>	No specific recommendations. If in doubt, get medical attention promptly.
-----------------------------	---

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

<b>Suitable extinguishing media</b>	Extinguish with foam, carbon dioxide or dry powder.
-------------------------------------	---

## BC Poxy 300 HD-AS Part-B

### 5.2. Special hazards arising from the substance or mixture

**Specific hazards** Irritating gases or vapors.

### 5.3. Advice for firefighters

**Protective actions during firefighting** Avoid breathing fire gases or vapors. Keep up-wind to avoid fumes. Do not use water jet as an extinguisher, as this will spread the fire. Control run-off water by containing and keeping it out of sewers and watercourses.

**Special protective equipment for firefighters** Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Warn everybody of potential hazards and evacuate if necessary. Provide adequate ventilation. Wear protective clothing as described in Section 8 of this safety data sheet. Avoid contact with skin and eyes. Do not breathe vapor.

### 6.2. Environmental precautions

**Environmental precautions** Avoid the spillage or runoff entering drains, sewers or watercourses. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up** Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers and seal securely. Containers with collected spillage must be properly labelled with correct contents and hazard symbol.

### 6.4. Reference to other sections

**Reference to other sections** Wear protective clothing as described in Section 8 of this safety data sheet.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

**Usage precautions** Use only in well-ventilated areas. Provide adequate ventilation. Open drum carefully as content may be under pressure. Avoid contact with skin and eyes. Avoid inhalation of vapors. Do not eat, drink or smoke when using the product. Good personal hygiene procedures should be implemented.

### 7.2. Conditions for safe storage, including any incompatibilities

**Storage precautions** Store in tightly-closed, original container in a dry, cool and well-ventilated place. Store away from incompatible materials (see Section 10).

### 7.3. Specific end use(s)

**Specific end use(s)** The identified uses for this product are detailed in Section 1.2.

## SECTION 8: Exposure Controls/personal protection

### 8.1. Control parameters

**Ingredient comments** No exposure limits known for ingredient(s).

### 8.2. Exposure controls

## BC Poxy 300 HD-AS Part-B

### Protective equipment



### Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

### Eye/face protection

The following protection should be worn: Chemical splash goggles or face shield. Personal protective equipment for eye and face protection should comply with European Standard EN166.

### Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. To protect hands from chemicals, gloves should comply with European Standard EN374. The selected gloves should have a breakthrough time of at least 8 hours.

### Other skin and body protection

Wear apron or protective clothing in case of contact.

### Hygiene measures

Provide eyewash station and safety shower. Keep away from food, drink and animal feeding stuffs. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Do not eat, drink or smoke when using the product. Change work clothing daily before leaving workplace.

### Respiratory protection

If ventilation is inadequate, suitable respiratory protection must be worn. Respirator selection must be based on exposure levels, the hazards of the product and the safe working limits of the selected respirator. Check that the respirator fits tightly and the filter is changed regularly. Wear a respirator fitted with the following cartridge: Gas filter, type A2. Half mask and quarter mask respirators with replaceable filter cartridges should comply with European Standard EN140.

## SECTION 9: Physical and Chemical Properties

### 9.1. Information on basic physical and chemical properties

<b>Appearance</b>	Liquid.
<b>Color</b>	Colorless to pale yellow.
<b>odor</b>	Ammonia.
<b>pH</b>	pH (concentrated solution): 8.5-10.5 @ 20 °C
<b>Melting point</b>	n/a°C
<b>Flash point</b>	>185°C
<b>Vapor pressure</b>	<1.2 mmHg @ °C
<b>Relative density</b>	1.01 @ 20 °C°C
<b>Solubility(ies)</b>	Slightly soluble in water.

### 9.2. Other information

<b>Other information</b>	Not available.
--------------------------	----------------

## SECTION 10: Stability and reactivity

**10.1. Reactivity :Acids**

## BC Poxy 300 HD-AS Part-B

### 10.2. Chemical stability

**Stability** Stable at normal ambient temperatures and when used as recommended.

### 10.3. Possibility of hazardous reactions

**Possibility of hazardous reactions** Not available.

### 10.4. Conditions to avoid

**Conditions to avoid** Heating may generate the following products: Toxic and corrosive gases or vapors. Avoid heat, flames and other sources of ignition. Avoid excessive heat for prolonged periods of time. Avoid exposure to high temperatures or direct sunlight.

### 10.5. Incompatible materials

**Materials to avoid** Avoid contact with acids.

### 10.6. Hazardous decomposition products

**Hazardous decomposition products** Fire or high temperatures create: Nitrous gases (NO<sub>x</sub>). Oxides of the following substances: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>). Vapors/gases/fumes of: Ammonia or amines.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### Acute toxicity - oral

**ATE oral (mg/kg)** 524.28

#### Acute toxicity - dermal

**ATE dermal (mg/kg)** 4,782.61

**Inhalation** This product is corrosive.

**Ingestion** Harmful if swallowed. Harmful: danger of serious damage to health by prolonged exposure if swallowed. Corrosive. Small amounts may cause serious damage.

**Skin contact** Causes burns. Corrosive. Prolonged contact causes serious tissue damage.

**Eye contact** Causes burns. Risk of serious damage to eyes.

**Acute and chronic health hazards** This product is corrosive. This product is corrosive. This product may cause skin and eye irritation. Prolonged contact may cause burns.

**Route of entry** Inhalation Skin absorption Ingestion.

**Target organs** Eyes Kidneys Liver Skin

## SECTION 12: Ecological Information

**Ecotoxicity** Avoid releasing into the environment. The product contains substances which are toxic to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

### 12.1. Toxicity

**Toxicity** Very toxic to aquatic organisms.

**Acute toxicity - aquatic invertebrates**

EC<sub>50</sub>, 48 hours: 15 mg/l, *Daphnia magna*

## BC Poxy 300 HD-AS Part-B

**12.2 Persistence and degradability** There are no data on the degradability

### 12.3. Bio accumulative potential

**Bio accumulative potential** LC50/96h/rainbow trout = >100 mg/L. LC50/48h/daphnia = 15 mg/L

### 12.4. Mobility in soil

**Mobility** Do not discharge into drains or watercourses or onto the ground.

### 12.5. Results of PBT and vPvB assessment

**Results of PBT and vPvB assessment** This product does not contain any substances classified as PBT or vPvB.

### 12.6. Other adverse effects

**Other adverse effects** Not available.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

**General information** When handling waste, the safety precautions applying to handling of the product should be considered.

**Disposal methods** Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

**Waste class** 08 04 99

## SECTION 14: Transport information

### 14.1. UN number

**UN No. (ADR/RID)** 2735

**UN No. (IMDG)** 2735

**UN No. (ICAO)** 2735

### 14.2. UN proper shipping name

**Proper shipping name (ADR/RID)** Amines, Liquid, Corrosive, N.O.S. (Poly(Oxy(Methyl-1,2-Ethanediy)),Alpha-(2-Am Omega-(2-Aminomethylethoxy, Diethyl methyl benzene diamine)

**Proper Shipping Name (Imdg)** Amines, Liquid, Corrosive, N.O.S. (Poly(Oxy(Methyl-1,2-Ethanediy)),Alpha-(2-Am Omega-(2-Aminomethylethoxy, Diethyl methyl benzene diamine)

**Proper Shipping Name (Icao)** Amines, Liquid, Corrosive, N.O.S. (Poly(Oxy(Methyl-1,2-Ethanediy)),Alpha-(2-Am Omega-(2-Aminomethylethoxy, Diethyl methyl benzenediamine)

**Proper Shipping Name (Adn)** Amines, Liquid, Corrosive, N.O.S. (Poly(Oxy(Methyl-1,2-Ethanediy)),Alpha-(2-Am Omega-(2-Aminomethylethoxy, Diethyl methyl benzenediamine)

### 14.3. Transport hazard class(es)

**ADR/RID class** 8

**ADR/RID label** 8

**IMDG class** 8

**ICAO class/division** 8

## BC Poxy 300 HD-AS Part-B

### Transport labels



#### 14.4. Packing group

ADR/RID packing group III

IMDG packing group III

ICAO packing group III

#### 14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant



#### 14.6. Special precautions for user

EmS F-A, S-B

Emergency Action Code 2X

Hazard Identification Number 80  
(ADR/RID)

Tunnel restriction code (E)

#### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**EU legislation** Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

#### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

### SECTION 16: Other information

Revision date 04/02/2023

Revision 1

Supersedes date 29/04/2021

## **BC Poxy 300 HD-AS Part-B**

**Hazard statements in full** EUH208 Contains BIS(1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL) SEBACATE. May produce an allergic reaction.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.