

## BC Poxy FC 1 45 -A

### SECTION 1:

Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product name BC Poxy FC 145 -A

Product number 394

#### 1.2. Relevant identified uses of the substance or mixture and uses

advised against

Identified uses Coating

#### 1.3. Details of the supplier of the safety data sheet

Building Chemistry Industry

P.Code 338941

Tel: 0138050533

Mob: 0593120221

Kingdom of Saudi Arabia

#### 1.4. Emergency telephone number Emergency telephone+0593120221

### SECTION 2:

Hazards identification

2.1. Classification of the substance or mixture Classification (EC 2008/1272)

Physical hazards Not Classified

Health hazards Acute Tox. 4 - H302 Skin Corr. 1B - H314 Eye Dam. 1 - H318

Elicitation - EUH208 STOT RE 2 - H373

Environmental hazards Aquatic Chronic 2 - H411

2.2. Label elements Pictogram



Signal word Danger

#### Building Chemistry Industry

3<sup>rd</sup> Industrial Area Dammam. Kingdom of Saudi Arabia.

Email: [info@bcisaudi.com](mailto:info@bcisaudi.com) Website: [www.bcisaudi.com](http://www.bcisaudi.com)



### Hazard statements:

EUH208 Contains BIS(1,2,2,6,6-PENTAMETHYL-4-PIPERIDYL) SEBACATE. May produce an allergic reaction.

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H373 May cause damage to organs through prolonged or repeated exposure. H411

Toxic to aquatic life with long lasting effects

### Precautionary statements:

P260 Do not breathe vapour/ spray.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/ shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P314 Get medical advice/ attention if you feel unwell

### Contains:

POLY(OXY(METHYL-1,2-ETHANEDIYL)), ALPHA-(2-AM OMEGA-(2-AMINOMETHYLETHOXY, DIETHYLMETHYLBENZENEDIAMINE

### Supplementary precautionary statements:

P264 Wash contaminated skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P321 Specific treatment (see medical advice on this label).

P363 Wash contaminated clothing before reuse. P391 Collect spillage.

P405 Store locked up.

P501 Dispose of contents/ container in accordance with national regulations

### Building Chemistry Industry

3<sup>rd</sup> Industrial Area Dammam. Kingdom of Saudi Arabia.

Email: [info@bcisaudi.com](mailto:info@bcisaudi.com) Website: [www.bcisaudi.com](http://www.bcisaudi.com)



### SECTION 3:

Composition/information on ingredients

#### Mixtures:

**POLY(OXY(METHYL-1,2-ETHANEDIYL)), ALPHA-(2-AM OMEGA-(2-AMINOMETHYLETHOXY**

CAS number: 9046-10-0

#### Classification

Acute Tox. 4 - H302 Skin Corr. 1B - H314

Aquatic Chronic 3 - H412

### SECTION 4:

#### General information:

Avoid contact with skin and eyes. Do not breathe vapour. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

#### Inhalation:

Move affected person to fresh air at once. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Get medical attention if any discomfort continues

#### Ingestion:

Do not induce vomiting. Give plenty of water to drink. Never give anything by mouth to an unconscious person. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention immediately.

Do not induce vomiting. Give plenty of water to drink. Never give anything by mouth to an unconscious person. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention immediately.

#### Eye contact:

Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes and get medical attention. Get medical attention if irritation persists after washing.

#### Building Chemistry Industry

3<sup>rd</sup> Industrial Area Dammam. Kingdom of Saudi Arabia.

Email: [info@bcisaudi.com](mailto:info@bcisaudi.com) Website: [www.bcisaudi.com](http://www.bcisaudi.com)



## SECTION 5:

Firefighting measures

### **Suitable extinguishing media:**

Extinguish with foam, carbon dioxide or dry powder

### **Specific hazards:**

Irritating gases or vapours.

### **Protective actions during:**

Avoid breathing fire gases or vapours. Keep up-wind to avoid fumes. Do not use water jet as

### **firefighting:**

an extinguisher, as this will spread the fire. Control run-off water by containing and keeping it out of sewers and watercourses.

### **Special protective equipment for firefighters:**

Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing

## SECTION 6:

Accidental release measures

### **Personal**

### **precautions:**

Warn everybody of potential hazards and evacuate if necessary. Provide adequate ventilation. Wear protective clothing as described in Section 8 of this safety data sheet. Avoid contact with skin and eyes. Do not breathe vapour.

### **Environmental precautions:**

Avoid the spillage or runoff entering drains, sewers or watercourses. Spillages or uncontrolled discharges into watercourses must be reported immediately to the Environmental Agency or other appropriate regulatory body.

### **Building Chemistry Industry**

3<sup>rd</sup> Industrial Area Dammam. Kingdom of Saudi Arabia.

Email: [info@bcisaudi.com](mailto:info@bcisaudi.com) Website: [www.bcisaudi.com](http://www.bcisaudi.com)



### Methods for cleaning up:

Methods for cleaning up Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers and seal securely. Containers with collected spillage must be properly labelled with correct contents and hazard symbol.

### Reference to other sections:

an extinguisher, as this will spread the fire. Control run-off water by containing and keeping it out of sewers and watercourses.

### SECTION 7:

Handling and storage

### Usage precautions:

Use only in well-ventilated areas. Provide adequate ventilation. Open drum carefully as content may be under pressure. Avoid contact with skin and eyes. Avoid inhalation of vapours. Do not eat, drink or smoke when using the product. Good personal hygiene procedures should be implemented.

### Storage precautions:

Store in tightly closed, original container in a dry, cool and well-ventilated place. Store away from incompatible materials (see Section 10).

### specific end use:

The identified uses for this product are detailed in Section 1.2.

### SECTION 8:

Exposure Controls/personal protection

### Ingredient comments:

No exposure limits known for ingredient(s).

### Protective equipment:



### Building Chemistry Industry

3<sup>rd</sup> Industrial Area Dammam. Kingdom of Saudi Arabia.

Email: [info@bcisaudi.com](mailto:info@bcisaudi.com) Website: [www.bcisaudi.com](http://www.bcisaudi.com)



### **Appropriate engineering controls:**

Provide adequate general and local exhaust ventilation

### **Eye/face protection:**

The following protection should be worn: Chemical splash goggles or face shield. Personal protective equipment for eye and face protection should comply with European Standard EN166.

### **Hand protection:**

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. To protect hands from chemicals, gloves should comply with European Standard EN374. The selected gloves should have a breakthrough time of at least 8 hours.

### **Other skin and body protection:**

Wear apron or protective clothing in case of contact

### **Hygiene measures:**

Provide eyewash station and safety shower. Keep away from food, drink and animal feeding stuffs. Good personal hygiene procedures should be implemented. Wash hands and any other contaminated areas of the body with soap and water before leaving the work site. Do not eat, drink or smoke when using the product. Change work clothing daily before leaving workplace.

### **Respiratory protection:**

If ventilation is inadequate, suitable respiratory protection must be worn. Respirator selection must be based on exposure levels, the hazards of the product and the safe working limits of the selected respirator. Check that the respirator fits tightly and the filter is changed regularly. Wear a respirator fitted with the following cartridge: Gas filter, type A2. Half mask and quarter mask respirators with replaceable filter cartridges should comply with European Standard EN140.

#### **Building Chemistry Industry**

3<sup>rd</sup> Industrial Area Dammam. Kingdom of Saudi Arabia.

Email: [info@bcisaudi.com](mailto:info@bcisaudi.com) Website: [www.bcisaudi.com](http://www.bcisaudi.com)



## SECTION 9:

Physical and Chemical Properties

### Appearance:

Liquid.

### Colour:

Colourless to pale yellow.

### Odour:

Ammonia.

### pH:

PH (concentrated solution): 20 @ 10.5-  
8.5 °C

### Solubility ies:

Slightly soluble  
in water

### Colour:

Colourless to pale yellow.

### Odour:

Ammonia.

### Relative:

20 @ 1.01 °C°C

## SECTION

Stability and reactivity

### Stability:

Stable at normal ambient temperatures and when used as  
recommended.

### Possibility of hazardous reactions:

Not available.

### Odour:

Ammonia.

### Building Chemistry Industry

3<sup>rd</sup> Industrial Area Dammam. Kingdom of Saudi Arabia.

Email: [info@bcisaudi.com](mailto:info@bcisaudi.com) Website: [www.bcisaudi.com](http://www.bcisaudi.com)



### Conditions to avoid:

PH (concentrated solution): 20 @10.5-8.5 °C

### Solubility ies:

Heating may generate the following products: Toxic and corrosive gases or vapours. Avoid heat, flames and other sources of ignition. Avoid excessive heat for prolonged periods of time. Avoid exposure to high temperatures or direct sunlight.

### Materials to avoid:

Avoid contact with acids.

### Hazardous decomposition products:

Fire or high temperatures create: Nitrous gases (NO<sub>x</sub>). Oxides of the following substances: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>). Vapours/gases/fumes of: Ammonia or amines

### PRODUCTS

Fire or high temperatures create: Nitrous gases (NO<sub>x</sub>). Oxides of the following substances: Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>). Vapours/gases/fumes of: Ammonia or amines.

### SECTION 11:

Toxicological  
information

#### Inhalation:

This product is corrosive.

#### Ingestion:

Harmful if swallowed. Harmful: danger of serious damage to health by prolonged exposure if swallowed. Corrosive. Small amounts may cause serious damage.

#### Skin contact:

Causes burns. Corrosive. Prolonged contact causes serious tissue damage

#### Eye contact:

Causes burns. Risk of serious damage to eyes.

### Building Chemistry Industry

3<sup>rd</sup> Industrial Area Dammam. Kingdom of Saudi Arabia.

Email: [info@bcisaudi.com](mailto:info@bcisaudi.com) Website: [www.bcisaudi.com](http://www.bcisaudi.com)



### **Acute and chronic health hazards:**

This product is corrosive. This product is corrosive. This product may cause skin and eye irritation. Prolonged contact may cause burns.

### **Route of entry:**

Inhalation Skin absorption Ingestion.

### **Target organs:**

Eyes Kidneys Liver Skin

### **SECTION 12:**

Ecological Information

### **Ecotoxicity:**

Avoid releasing into the environment. The product contains substances which are toxic to aquatic organisms, and which may cause long-term adverse effects in the aquatic environment.

### **Toxicity:**

Very toxic to aquatic organisms.

### **Acute toxicity - aquatic invertebrates:**

Toxicological  
information

### **Mobility:**

Do not discharge into drains or watercourses or onto the ground

### **Results of PBT and vPvB assessment:**

This product does not contain any substances classified as PBT or vPvB.

### **Other adverse effects:**

Not available.

### **SECTION 13:**

Disposal considerations.

### **General information:**

When handling waste, the safety precautions applying to handling of the product should be considered.

### **Building Chemistry Industry**

3<sup>rd</sup> Industrial Area Dammam. Kingdom of Saudi Arabia.

Email: [info@bcisaudi.com](mailto:info@bcisaudi.com) Website: [www.bcisaudi.com](http://www.bcisaudi.com)



### **Disposal methods:**

Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

### **SECTION 14:**

Transport information.

#### **Proper Shipping Name (IMDG):**

Amines, Liquid, Corrosive, N.O.S. (Poly (Oxy(Methyl-1,2-Ethanediy)),Alpha-(2-Am Omega-(2-Aminomethylethoxy, Diethyl methyl benzene diamine)

#### **Proper Shipping Name (Icao):**

Amines, Liquid, Corrosive, N.O.S. (Poly (Oxy(Methyl-1,2-Ethanediy)),Alpha-(2-Am Omega-(2-Aminomethylethoxy, Diethyl methyl benzenediamine)

#### **Proper Shipping Name (Adn):**

Amines, Liquid, Corrosive, N.O.S. (Poly (Oxy(Methyl-1,2-Ethanediy)),Alpha-(2-Am Omega-(2-Aminomethylethoxy, Diethyl methyl benzenediamine) **SECTION 15:**

Regulatory information

#### **EN legislation:**

Regulation (EC) No 2008/1272 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

#### **Chemical safety assessment:**

No chemical safety assessment has been carried out.

### **SECTION 16:**

Other information

#### **Building Chemistry Industry**

3<sup>rd</sup> Industrial Area Dammam. Kingdom of Saudi Arabia.

Email: [info@bcisaudi.com](mailto:info@bcisaudi.com) Website: [www.bcisaudi.com](http://www.bcisaudi.com)



### **Hazard statements in full:**

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction.

H318 Causes serious eye damage. H319 Causes serious eye irritation.

H373 May cause damage to organs through prolonged or repeated exposure. H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

### **Revision date:**

2023/02/04

### **Supersedes date:**

2021/04/29

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.

### **Building Chemistry Industry**

3<sup>rd</sup> Industrial Area Dammam. Kingdom of Saudi Arabia.

Email: [info@bcisaudi.com](mailto:info@bcisaudi.com) Website: [www.bcisaudi.com](http://www.bcisaudi.com)

